



PRODUCT SPECIFICATION - STRAIGHT ADAPTER

PRODUCT LIST

PRODUCT DIMENSIONS

MODEL	DIMENSIONS	ROUND EQUIV.	ROUND TRANSVERSE AREA. (SQ. IN.)	A	B	C	D	E	F	G
CP-SPA05	3"x5"x9"	4"	12.724	3.269"	5.269"	4.5"	10 GA.	5"	2"	3"
CP-SPA08	3"x8"x11"	5"	20.040	3.269"	8.269"	5.563"	10 GA.	8"	4"	3"
CP-SPA12	3"x12"x13"	6"	28.886	3.269"	12.269"	6.625"	10 GA.	12"	6"	3"
CP-SPA14	4"x14"x15"	8"	50.014	4.269"	14.269"	8.625"	10 GA.	14"	8"	4"
CP-SPA17	3"x17"x15"	8"	50.014	3.269"	17.269"	8.625"	10 GA.	17"	8"	3"
CP-SPA27	3"x27"x17"	10"	78.814	3.269"	27.269"	10.625"	10 GA.	27"	10"	3"
CP-SPA22	4"x22"x17"	10"	78.814	4.269"	22.269"	10.625"	10 GA.	22"	10"	4"

MATERIAL: 10 GAUGE GALVANIZED A653 G90 MEETS ASTM A-653. TENSILE STRENGTH 50,000.0 YIELD 36,000.
 ALL WELDS WILL BE SPRAYED, ROLLED OR BRUSHED WITH GALVANIZED #90 COATING.
 RECTANGULAR CONNECTION: MASTIC, CAULKING, EPOXY BINDING OR OTHER APPROVED METHOD.
 ROUND CONNECTION: CAST IRON/PLASTIC PIPE CONNECTION USE CAST IRON OR PLASTIC TO STEEL COUPLINGS.

REV	ZONE	DATE	REVISION DESCRIPTION	BY	CK'D



9421 Monterey Ave. Bellflower, CA. 90706 - Office (714)903-2468

SCALE: NONE	DRAWN BY JB	DATE 08/18/16	CHECKED BY JB	APPROVED BY JB
-------------	-------------	---------------	---------------	----------------

RECTANGULAR STEEL PIPE AND FITTINGS.
 STRAIGHT ADAPTER